



# THE RESITECH GROUP

Shed 20A/17 River Road REDBANK QLD 4301 PO BOX 3116 BIRKDALE QLD 4159

Phone: 07 3822 8233 Fax: 07 3207 5971 Email: info@theresitechgroup.com

Specialists in Plastics Recycling & Plastic Sheet Extrusion Products

## TECHNICAL DATA SHEET

### "DRY-MATE" DAMPCOURSE PRODUCT

#### **DESCRIPTION:**

**"Dry-Mate"** is a Polyethylene Dampcourse and Concealed Flashing barrier of impervious material, built-in to prevent moisture movement to any part of a building requiring protection. It includes a waterproof strip barrier around an opening in a wall or door or at a roof junction.

#### **AREAS OF USE:**

Used in the building industry to avoid moisture. It provides a complete and permanent moisture barrier in the protection against water damage to buildings through the walls and brickwork. Used around brick vents, timber framing, windows and door flashing.

#### **FEATURES AND BENEFITS:**

- Unique construction of "DRY-MATE" gives instant shape forming
- A replacement for Bitumen Paper
- Does not react with solvent treated timber
- Inert to most solvents
- Permanent life span as non-degradable
- Easy to use
- Cost effective

#### **SPECIFICATION:**

Dampcourse rolls shall consist of LDPE flexible material with an impact resistance in accordance with AS/NZS2904. Carbon black ration of +/-2.5%

#### **HEALTH AND SAFETY:**

Safety Precautions:

Avoid Excessive Heat

Strong Oxidising Agents

For detailed information click here to view **Material Safety Data Sheet**.

#### **TECHNICAL DATA:**

- Manufactured to AS/NZS2904 – 1995
- Type Testing – Amdel 96L2563
- Extruded Sheet – Polyethylene material smooth to 500µM thickness (0.5mm thick)
- Embossed both sides – effective thickness 750µM (0.75mm thick)
- Impact resistant
- Black Flexible Polyethylene Film
- Low slip with a kinetic coefficient of friction
- Non-Slip as product is double embossed
- Roll core made from recycled plastic



# THE RESITECH GROUP

Shed 20A/17 River Road REDBANK QLD 4301 PO BOX 3116 BIRKDALE QLD 4159

Phone: 07 3822 8233 Fax: 07 3207 5971 Email: info@theresitechgroup.com

**Specialists in Plastics Recycling & Plastic Sheet Extrusion Products**

## **PACKAGING AND STORAGE:**

- **"Dry-Mate"** Rolls are available in Boxes, Pallets or singular rolls
- Product is available labelled to your company's specification
- Product will be labelled with a Product Identification label for QA purposes,
- Stored undercover and enclosed to avoid dust.
- Sizes available:
  - 50mm - 600mm x 20m rolls
  - 110mm - 600mm x 30m rolls
  - 110mm - 450mm x 50m rolls
  - 150mm - 600mm x 100m rolls

## **APPLICATION GUIDE:**

Application Procedure and Equipment:

Brick Application: Unroll and lay flat against surfaces to be waterproofed and apply mortar both sides to better stability.

Window Application: Unroll roll and follow window shape to be waterproofed, and then adhere to window surface with either staple or adhesive for permanent fixture.

Click here to view **Application Brochure**.

## **DISCLAIMER:**

The information provided by Resitech in relation to Resitech goods or their use is in good faith, which has been compiled from various sources and is believed by Resitech to be appropriate and reliable. The actual use and application of the goods will vary with application conditions which are beyond our control. Resitech makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information.