



THE RESITECH GROUP

Shed 20A/17 River Road REDBANK QLD 4301 PO BOX 3116 BIRKDALE QLD 4159

Phone: 07 3822 8233 Fax: 07 3207 5971 Email: info@theresitechgroup.com

Specialists in Plastics Recycling & Plastic Sheet Extrusion Products

MATERIAL SAFETY DATA SHEET

LOW DENSITY POLYETHYLENE – LDPE

PRODUCT IDENTIFICATION

Product: Low Density Polyethylene - LDPE
Uses: Extrusion.
Physical Appearance: Black Die Face Cut Pellets, approx. 5-6mm diameter
Ingredients: Post Industrial low density. Carbon black Masterbatch.
Melting Point: 170° - 190°
Specific Gravity: 0.92

SAFE HANDLING INFORMATION

Storage and Transport: Not classified as dangerous goods.
Spills and Disposal:

1. If on fire use correct fire extinguisher to prevent spreading.
2. Shovel or sweep up spills into a container.
3. Dispose in accordance with local government regulations.
4. Dispose of or recycle.
5. Be wary of static electricity build up.

PELLET SPILLS ON FLOORS WILL CREATE A SLIP HAZARD